

Received: from mailhub.watson.ibm.com (9.2.250.97) by yktvmv.watson.ibm.com
(IBM VM SMTP V2R4) with TCP; Mon, 24 Nov 97 12:53:32 EST
Received: from igw2.watson.ibm.com (igw2.watson.ibm.com [9.2.250.12]) by mailhub
Received: from prod.lexis-nexis.com (prod.lexis-nexis.com [138.12.4.30]) by igw2
Received: by prod.lexis-nexis.com id AA13249
(InterLock SMTP Gateway 3.0 for dmmorris@watson.ibm.com);
Mon, 24 Nov 1997 12:53:35 -0500
Message-Id: <199711241753.AA13249@prod.lexis-nexis.com>
Received: by prod.lexis-nexis.com (Internal Mail Agent-1);
Mon, 24 Nov 1997 12:53:35 -0500
Date: Mon, 24 Nov 97 12:53:34 EST
From: lexis-nexis@prod.lexis-nexis.com (LEXIS(R)/NEXIS(R) Print Delivery)
To: dmmorris@watson.ibm.com
Subject: LEXIS(R)/NEXIS(R) Print Request Job 53252, 1 of 1

MORRIS, DAN
IBM CORPORATION
YORKTOWN PATENT OPERATIONS
T. J. WATSON RESEARCH CENTER
P.O. BOX 218
YORKTOWN HEIGHTS, NEW YORK 10598-0218
MAIL-IT REQUESTED: NOVEMBER 24, 1997

100G6J

CLIENT: 98774
LIBRARY: LEXPAT
FILE: UTIL

YOUR SEARCH REQUEST AT THE TIME THIS MAIL-IT WAS REQUESTED:
CLAIMS(PEROVSKITE W/1 LIKE OR PEROVSKITE W/1 TYPE)

NUMBER OF PATENTS FOUND WITH YOUR REQUEST THROUGH:
LEVEL 1... 2

LEVEL 1 PRINTED

DISPLAY FORMAT: KWIC

SEND TO: MORRIS, DAN
IBM CORPORATION
YORKTOWN PATENT OPERATIONS
T. J. WATSON RESEARCH CENTER
P.O. BOX 218
YORKTOWN HEIGHTS NEW YORK 10598-0218

*****03460*****

LEVEL 1 - 1 OF 2 PATENTS

5,134,042

<=2> GET 1st DRAWING SHEET OF 6

Jul. 28, 1992

Solid compositions for fuel cells, sensors and catalysts

INVENTOR: Madou, Marc J., Palo Alto, California
Otagawa, Takaaki, Fremont, California
Sher, Arden, Foster City, California

... [*12] selected from lanthanum, cerium, neodymium, praseodymium, or scandium, B is independently selected from strontium, calcium, barium or magnesium, Q is independently selected from nickel, cobalt, iron or manganese, and y is between about 0.0001 and 1, wherein the perovskite or perovskite-type structure has an average size and distribution of between about 50 and 200 Angstroms in diameter; and the composite layer of between about 25 and 1000 microns in thickness;

said composite having multiple interfaces between:

...

LEVEL 1 - 2 OF 2 PATENTS

PAGE

4,948,680

<=2> GET 1st DRAWING SHEET OF 26

Aug. 14, 1990

Solid compositions for fuel cell electrolytes

INVENTOR: Madou, Marc J., Palo Alto, California
Otagawa, Takaaki, Fremont, California
Sher, Arden, Foster City, California

... [*25] 1.5 and d is between 0.001 and less than or equal to 3,

wherein either the first electrode material (C) or second electrode material (A') comprises

A 1 - x B x QO 3

having a perovskite or perovskite-type structure as an electrode catalyst in combination with

A 1 - x B x Z

as a polycrystalline solid electrolyte wherein

A is independently selected from lanthanum, cerium, neodymium, praseodymium or scandium,

...

* 2 PAGES

36 LINES

JOB 53252 100G6J

*

* 12:53 P.M. STARTED

12:53 P.M. ENDED

11/24/97

*